



LP-1 series (Ver.1.6)

Thermal Label Printing Scale

- Up to 4000 PLU Capacity
- Up to 1000 Message (Ingredient)
- 54 Preset Keys
- 30 Standard Label Formats
- Manager Program (PC)
 - Logo Image Printing
 - 6 Free Format Label Storage
 - Various Barcode Format



CAS
S · C · A · L · E

LP-1 series (Ver.1.6)

Thermal Label Printing Scale

FEATURES

- Memory Capacity : 4000PLU, 1000Message
- PLU Data Items : Commodity Name , Message
Item No., Tare Weight, Unit Price, Group Code
- Printing Items : Commodity Name, Message
Packed-on Date, Sell-by Date, Unit Price, Weight
Total Price, Store Name & Address, Serial No.
Time, PLU No., Group Code
- 54 Preset Keys for Frequent Transaction Items
- Easy Programming with Wide Keyboard
- Pre-pack Mode for Automatic Weighing/Labeling
- Printing Detailed Report for Each Item
- Wide Tray and Clear Display Board
- High-Speed and Low-Noise Thermal Barcode
Printer
- Free Format Label Design
 - Bar Code : IAN8, I2of5, UPC13A, UPC13A2
UPC13A5, EAN8A2, EAN8A5,
EAN13, EAN13A2, EAN13A5



Pole Display Type

SPECIFICATIONS

Model	LP series
Weighing Capacity	6 × 0.002kg, 15 × 0.005kg, 30 × 0.01kg
Display Digit	5 / 6 / 7 (Weight / Unit Price / Total Price)
External Interface	RS 232C(Standard), TCP/IP (Option)
Measurement Type	Load Cell
Printing Type	Thermal Print
Preset Data	4000PLU, 1000 Message (50 Char × 8 Line)
Label Size	58 × 30mm ~ 58 × 100mm
Power Source	AC 110/120/220/240V, 50/60Hz
Power Consumption	Max. 100W
Operating Temperature	-10°C ~ +40°C
Platter Size (mm)	400(W) × 245(D)
Dimensions (mm)	410(W) × 430(D) × 197(H)
Product Weight	13kg

OPTIONS

- TCP/IP
- Pole Display
- PC Manager Program
- Dual Range
- Interface Cable



CAS BLDG., # 440-1, SUNGNAE-DONG,
GANGDONG-GU, SEOUL, KOREA
TEL : 82-2-2225-3500
FAX : 82-2-475-4668
<http://www.cas.co.kr>

Specifications are subject to change for improvement without prior notice.

LABEL FORMATS

(50% Of Original Size)



DIMENSIONS

Unit: mm

