

ELTRADE[®]

MAXIMUM RELIABILITY

ELTRADE A1

ELECTRONIC CASH REGISTER



- ▶ **COMPACT CASH REGISTER, SUITABLE FOR SMALL BUSINESSES AND MOBILE USAGE**
- ▶ **ROBUST DESIGN FOR EXTREME WORKING CONDITIONS**

www.eltrade.com

Applications

ELTRADE A1 is a modern electronic cash register device with ergonomic design and powerful hardware. The device is designed for mobile usage and the integrated Bluetooth is allowing wireless connection to any PDA devices for printing of receipts. ELTRADE A1 is equipped with Easy-load printing mechanism, convenient belt clip and two graphic displays with adjustable backlight. The device is using high-performance 32-bit processor and the failproof operating system of ELTRADE Ltd. The work of with the cash register is intuitive and easy due to the user-friendly menus and navigation options.

ELTRADE A1 allows direct connection of USB keyboard or barcode reader due to the integrated USB On-The-Go port.

The device supports variety of additional functions and features like printing of logos for the PLUs, printing of barcodes, insertion of comments for the sold items, etc. ELTRADE A1 supports periodical reports by PLUs, departments, VAT groups and payment types. ELTRADE Ltd. is also providing various drivers for integration of the fiscal devices with the commercial software products, popular on the market.

Special features

ELTRADE A1 is designed to withstand extreme working conditions like:

- ▶ Frequent disturbances in the electric network
- ▶ Operating temperatures from 0 °C to 45 °C
- ▶ Storage temperatures from -25 °C to 55 °C
- ▶ Extreme dust conditions
- ▶ Extreme humidity conditions



Functional features

ELTRADE A1 supports

- ▶ 30 000 PLUs
- ▶ 50 departments
- ▶ 30 PLU groups
- ▶ 11 types of payment
- ▶ 30 operators
- ▶ Logo printing on the receipt

Technical features

- ▶ Dimensions 195 / 95 / 50 mm
- ▶ Built-in GPRS module
- ▶ Thermal printing, Easy-load printing mechanism
- ▶ Printing speed: 75 mm/sec
- ▶ Graphic LCD displays with backlight
- ▶ Electronic journal capacity - 4 GB
- ▶ Consumables - thermopaper 57/13 m
- ▶ Li - ion battery 7.4V / 1600 mAh
- ▶ External antenna connector (optional)
- ▶ Power supply: DC 12V / 2 A

Communication features

Available interfaces:

- ▶ RS232 interface - for connection to PC, electronic scale and RS232 barcode reader
- ▶ USB 2.0 OTG - for connection to PC, standard USB keyboard and USB barcode reader
- ▶ Cash drawer management connector
- ▶ GPRS connection
- ▶ Bluetooth connection (optional)

